

iADEA XMP 330

The XMP-330 meets the industry's highest standards for hardware video decoding performance. Advanced HDMI connectivity delivers Full HD 1080p video and audio output digitally over a single cable. Support for S1 to S12 media profiles, as defined by POPAI, the industry's standards establishing organization, simplifies device selection and content creation.

HIGHLIGHTS

- Fanless Full-HD 1080p decoding
- Plug-and-play professional signage
- Works with your management solution



PLAYBACK CONTROL

- W3C SMIL 3.0 instructions (sub-set)
- Real-time clock playlist events
- Network playlist sync
- USB direct sync

LOCAL STORAGE

- 4 GB flash memory (approx. 90 minutes of typical high def. video @5 Mbps)
- CF card slot (card replaces internal storage)

DIGITAL SIGNAGE FEATURES

- Auto-play starts playing scheduled contents automatically whenever power is re-established
- Automatic error recovery with WDT
- Real-time clock with clock battery
- Automatic NTP keeps time and date in sync
- Screw-lock connectors for reliable installation

PORT CONNECTORS

- HDMI 1.3a (Full-HD 1080p with audio)
- D-SUB VGA connector
- 3.5mm combined analog A/V out
- Ethernet 10/100 BASE-T
- USB 2.0 High Speed host x 2